





PRODUCT DESCRIPTION

Introducing the new EZ Fabric Counter display, developed to combine convenience and show. Push button snaps connect the lightweight aluminum framework together. Slip the fabric over the frame, hook and loop the fabric piece underneath and zip shut the backside, attach counter top, Graphics available on front, back, sides and top. See your printed graphic through the frosted acrylic counter top piece! this fully enclosed unit unzips to make for a convenient spot to hide stuff. Carry Nylon Bag included. With the 4 Section, four Curved frames are secured together to create a much larger width and longer curve around. Graphic wraps around the entire structure.

DISPLAY DIMENSION	94" W x 38" H x 63.5" L
RAPHIC DIMENSIONS	230" W x 40" H

GRAPHIC MATERIAL

Stretch Fabric

GRAPHIC FINISHING

One piece, Inside hem. Two top zippers.

DISPLAY CONSTRUCTION

Aluminum Frame Acrylic Counter Top

SHIPIPING WEIGHTS & DIMENSIONS

51 lbs (2 frames only) 53 lbs (2 frames with graphic)

Shipping Dimensions 2 @ 50" H x 21" W x 14" D

LARGE QUANTITY FREIGHT

Freight Shipping	12 boxes per 49" L x 40" W x 62" H skids
Freight Weight	675 lbs (frames) 669 lbs (frames & graphic)

GRAPHIC TURN AROUND TIME

2 business days after proof approval

AVAILABLE ACCESSORIES

Curved Shelf

AVAILIBILITY	CA and PA
TOP WEIGHT CAPACITY	75 lbs
SHELF WEIGHT CAPACITY	7 lbs



Screw & Wingnut Frame Connection



Nylon Carry Bag



Optional Curved Shelf



PARTS LIST



Qty 4 - Top Base (Pre-drilled for acrylic counter)



Qty 16 - 33" Vertical Support Bar




Qty 4 - Acrylic Top Counter



Qty 12 - Screw & Wingnut



Qty 4 - Bottom Base



Qty 8 - 13.25" Horizontal Support Bar



Qty 8 - Large Head Bolt




REQUIRED TOOLS



Flathead Screwdriver*



Insert head bolt.



Then screw and tighten.



SET UP INSTRUCTIONS 1/2

Step1

First, start by building both vertical sides of the EZ Fabric Counter.



Step 3

Set out your bottom base on a flat surface. Be sure not to confuse this base with the top, which has (2) pre-drilled holes for the acrylic counter top. Locate the push-out caps on the inside of the posts.



Step 5

The frame is now ready for the top base. Make sure it appears as shown above.



Step 7

Be sure that there is (1) pre-drilled hole on each side, facing up on the top base.



Step 2

Take (2) 33"support bars and (1) 13.25" support bar and connect them as shown above. Repeat the same process for another set.



Step 4

Push in and then hold the push-out cap on the bottom base so the support bar will slide on. Now slide each bar completely on to the bottom base. You will slide in one push-out cap at a time.



Step 6

Slide on the top base just as mentioned in step 4.



Step 8

Complete the first frame.





SET UP INSTRUCTIONS 2/2

Step 9

Repeat same process for the other 3 frames and place frames side by side.



Step 1

Starting from the bottom, slide the graphic on to the frame.



Step 13

Locate the pre-drilled hole on the top base. Make sure this hole aligns with the finished hole on the graphic.




Step 15

The install is now complete.



Step 10

Connect frames with bolts and wing nuts.



Step 12

Zip up the graphic around the frame.



Step 14

Align the acrylic counter top holes and insert the large head screws to secure the counter top to the frame.

